

Предохранительные клапаны

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)3454-704
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)3454-704

Беларусь +375-257-127-88

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: tec@nt-rt.ru || сайт: <https://tiemme.nt-rt.ru/>



1917 1927

Safety valve female connections

TECHNICAL SPECIFICATIONS

- Min operating temperature: -5°C
- Max operating temperature: 120°C
- Nominal pressure: PN10
- Body material: Brass CW617N
- Opening overpressure: 10%
- Connection threads: ISO 228 female

Code	Type	Calibration	Price €	Unit/Box
192 0013	1/2" x 1/2"	1.5 bar		1/40
192 0033	1/2" x 1/2"	1.8 bar		1/40
192 0025	1/2" x 1/2"	2 bar		1/40
192 0008	1/2" x 1/2"	2.5 bar		1/40
192 0001	1/2" x 1/2"	3 bar		1/40
192 0060	1/2" x 1/2"	3.5 bar		1/40
192 0010	1/2" x 1/2"	4 bar		1/40
192 0053	1/2" x 1/2"	5 bar		1/40
192 0006	1/2" x 1/2"	6 bar		1/40
192 0022	1/2" x 1/2"	7 bar		1/40
192 0035	1/2" x 1/2"	8 bar		1/40
192 0011	1/2" x 1/2"	9 bar		1/40
192 0018	1/2" x 1/2"	10 bar		1/40
192 0014	3/4" x 3/4"	1.5 bar		1/40
192 0027	3/4" x 3/4"	1.8 bar		1/40
192 0034	3/4" x 3/4"	2 bar		1/40
192 0012	3/4" x 3/4"	2.5 bar		1/40
192 0003	3/4" x 3/4"	3 bar		1/40
192 0054	3/4" x 3/4"	3.5 bar		1/40
192 0015	3/4" x 3/4"	4 bar		1/40
192 0071	3/4" x 3/4"	5 bar		1/40
192 0007	3/4" x 3/4"	6 bar		1/40
192 0036	3/4" x 3/4"	7 bar		1/40
192 0030	3/4" x 3/4"	8 bar		1/40
192 0043	3/4" x 3/4"	9 bar		1/40
192 0031	3/4" x 3/4"	10 bar		1/40
192 0072	1" x 1"	1.5 bar		1/25
192 0073	1" x 1"	1.8 bar		1/25
192 0074	1" x 1"	2 bar		1/25
192 0075	1" x 1"	2.5 bar		1/25
192 0004	1" x 1"	3 bar		1/25
192 0076	1" x 1"	3.5 bar		1/25

1917-1927 - Safety valve female connections

Code	Type	Calibration	Price €	Unit/Box
192 0023	1" x 1"	4 bar		1/25
192 0077	1" x 1"	5 bar		1/25
192 0009	1" x 1"	6 bar		1/25
192 0016	1" x 1"	7 bar		1/25
192 0026	1" x 1"	8 bar		1/25



1918 1928

Safety valve male-female connections

TECHNICAL SPECIFICATIONS

- Min operating temperature: -5°C
- Max operating temperature: 120°C
- Nominal pressure: PN10
- Body material: Brass CW617N
- Opening overpressure: 10%
- Connection threads: ISO 228 male-female

Code	Type	Calibration	Price €	Unit/Box
192 0052	1/2" x 1/2"	1.5 bar		1/40
192 0078	1/2" x 1/2"	1.8 bar		1/40
192 0045	1/2" x 1/2"	2 bar		1/40
192 0041	1/2" x 1/2"	2.5 bar		1/40
192 0002	1/2" x 1/2"	3 bar		1/40
192 0055	1/2" x 1/2"	3.5 bar		1/40
192 0020	1/2" x 1/2"	4 bar		1/40
192 0059	1/2" x 1/2"	5 bar		1/40
192 0005	1/2" x 1/2"	6 bar		1/40
192 0029	1/2" x 1/2"	7 bar		1/40
192 0037	1/2" x 1/2"	8 bar		1/40
192 0050	1/2" x 1/2"	9 bar		1/40
192 0038	1/2" x 1/2"	10 bar		1/40
192 0086	1" x 1"	1.5 bar		1/25
192 0087	1" x 1"	1.8 bar		1/25
192 0088	1" x 1"	2 bar		1/25
192 0089	1" x 1"	2.5 bar		1/25
192 0090	1" x 1"	3 bar		1/25
192 0091	1" x 1"	3.5 bar		1/25
192 0092	1" x 1"	4 bar		1/25
192 0093	1" x 1"	5 bar		1/25
192 0102	1" x 1"	6 bar		1/25
192 0019	1" x 1"	7 bar		1/25
192 0024	1" x 1"	8 bar		1/25



1917M 1927M

Safety valve female connections with increased outlet

TECHNICAL SPECIFICATIONS

- Min operating temperature: -5°C
- Max operating temperature: 120°C
- Nominal pressure: PN10
- Body material: Brass CW617N
- Opening overpressure: 10%
- Connection threads: ISO 7 female

+ INCREASED OUTLET

Code	Type	Calibration	Price €	Unit/Box
192 0066	1/2" x 3/4"	1.5 bar		1/40
192 0067	1/2" x 3/4"	1.8 bar		1/40
192 0048	1/2" x 3/4"	2 bar		1/40
192 0042	1/2" x 3/4"	2.5 bar		1/40
192 0040	1/2" x 3/4"	3 bar		1/40
192 0068	1/2" x 3/4"	3.5 bar		1/40
192 0069	1/2" x 3/4"	4 bar		1/40
192 0070	1/2" x 3/4"	5 bar		1/40
192 0039	1/2" x 3/4"	6 bar		1/40
192 0057	1/2" x 3/4"	7 bar		1/40
192 0096	1/2" x 3/4"	8 bar		1/40
192 0097	1/2" x 3/4"	9 bar		1/40
192 0098	1/2" x 3/4"	10 bar		1/40



1917MAN 1927MAN

Safety valve female connections with 1/4" pressure gauge connection

TECHNICAL SPECIFICATIONS

- Min operating temperature: -5°C
- Max operating temperature: 120°C
- Nominal pressure: PN10
- Body material: Brass CW617N
- Opening overpressure: 10%
- Connection threads: ISO 228 female

+ WITH PRESSURE GAUGE CONNECTION

i Accessory: Manometer art. 2080POST see page 14

Code	Type	Calibration	Price €	Unit/Box
192 0061	1/2" x 1/2"	1.5 bar		1/40
192 0062	1/2" x 1/2"	1.8 bar		1/40
192 0063	1/2" x 1/2"	2 bar		1/40
192 0046	1/2" x 1/2"	2.5 bar		1/40
192 0028	1/2" x 1/2"	3 bar		1/40
192 0064	1/2" x 1/2"	3.5 bar		1/40
192 0044	1/2" x 1/2"	4 bar		1/40
192 0065	1/2" x 1/2"	5 bar		1/40
192 0058	1/2" x 1/2"	6 bar		1/40
192 0051	1/2" x 1/2"	7 bar		1/40
192 0094	1/2" x 1/2"	8 bar		1/40
192 0095	1/2" x 1/2"	9 bar		1/40
192 0056	1/2" x 1/2"	10 bar		1/40



1918MAN 1928MAN

Safety valve male-female connections with 1/4" pressure gauge connection

TECHNICAL SPECIFICATIONS

- Min operating temperature: -5°C
- Max operating temperature: 120°C
- Nominal pressure: PN10
- Body material: Brass CW617N
- Opening overpressure: 10%
- Connection threads: ISO 228 male-female

+ WITH PRESSURE GAUGE CONNECTION

i Accessory: Manometer art. 2080POST see page 14

Code	Type	Calibration	Price €	Unit/Box
192 0079	1/2" x 1/2"	1.5 bar		1/40
192 0080	1/2" x 1/2"	1.8 bar		1/40
192 0081	1/2" x 1/2"	2 bar		1/40
192 0082	1/2" x 1/2"	2.5 bar		1/40
192 0032	1/2" x 1/2"	3 bar		1/40
192 0083	1/2" x 1/2"	3.5 bar		1/40
192 0084	1/2" x 1/2"	4 bar		1/40
192 0085	1/2" x 1/2"	5 bar		1/40
192 0049	1/2" x 1/2"	6 bar		1/40
192 0047	1/2" x 1/2"	7 bar		1/40
192 0099	1/2" x 1/2"	8 bar		1/40
192 0100	1/2" x 1/2"	9 bar		1/40
192 0101	1/2" x 1/2"	10 bar		1/40



1916

Temperature and pressure safety valve male/copper pipe outlet connection

TECHNICAL SPECIFICATIONS

- Operating temperature: between 90 and 95°C.
- Operating pressure: 3-4-6-7 bar
- Nominal pressure PN 10
- Fluid: Water
- Body material: Brass CW617N
- Complies with European standard EN 1490 and Directive 97/23/EC (PED)

+ TEMPERATURE-PRESSURE CONTROL

Code	Type	Calibration	Price €	Unit/Box
192 0106	1/2" x 15	3 bar		1/10
192 0107	1/2" x 15	4 bar		1/10
192 0108	1/2" x 15	6 bar		1/10
192 0109	1/2" x 15	7 bar		1/10
192 0111	3/4" x 15	3 bar		1/10
192 0112	3/4" x 15	4 bar		1/10
192 0113	3/4" x 15	6 bar		1/10
192 0114	3/4" x 15	7 bar		1/10
192 0116	3/4" x 22	3 bar		1/10
192 0117	3/4" x 22	4 bar		1/10
192 0118	3/4" x 22	6 bar		1/10
192 0119	3/4" x 22	7 bar		1/10

По вопросам продаж и поддержки обращайтесь:

Алматы (727)3454-704
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)3454-704

Беларусь +375-257-127-88

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: tec@nt-rt.ru || сайт: <https://tiemme.nt-rt.ru/>